

Safety Data Sheet

Conventional & Maintenance Free (MF), Dry Charged Lead Battery

According to Regulation (EC) No 2015/830

Version 3.0 Issue date: 02/12/2019

Section 1 Identification of the substance/mixture and o	of the compan	y/undertaking
---	---------------	---------------

1.1 Product identifier:	
Product Form :	Article
Product name :	Maintenance Free (MF), VRLA (MF), Conventional series – Dry Charge Lead Battery
1.2 Relevant identified uses of the substa	ance and uses advised against:
1.2.1 Identified uses:	Motorcycle and power sport starter battery
1.2.2 Uses advised against:	Not available.
1.3 Details of the supplier of the safety da	ata sheet:
Supplier:	FULBAT S.a.s
Address:	23 bis rue Edouard Nieuport
	92150 Suresnes
	France
Telephone:	(France) +33 1 83 62 45 55
1.4 Emergency telephone Number:	
CHEMTREC(US, Canada & Mexico)	0086-1-800-424-9300
CHEMTREC (International)	0086-1-703-527-3887
Available outside office hours?	YES NO X

Section 2 Hazards Identification

2.1 Classification of the substance/mixture:

2.1.1 Classification:

The mixture is classified as following according to REGULATION (EC) No 1272/2008:

REGULATION (EC) No 2015/830		
Reproductive toxicity, Category 1A	H360Fd	
Specific target organ toxicity (repeated exposure) Category 1A H372		
Hazardous to the aquatic environment -Acute Hazard, Category 1 H400		
Hazardous to the aquatic environment - Chronic Hazard, Category 1	H410	

For full text of H- phrases: see section 16.



2.2 label elements:

Hazard Pictograms:





GHS08

GHS09

Signal Word(S): Danger

Hazard Statement: H360Fd - May damage fertility. Suspected of damaging the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

Precautionary statement: P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust/fume/gas/mist/vapours/spray

P264 - Wash ... thoroughly after handling

P270 - Do not eat, drink or smoke wfien using this product

P273 - Avoid release to the environment

2.3 Other hazards: Lead may be toxic to blood, kidneys, central nervous system

Section 3 Composition/information on ingredients

Substance/Mixture: Mixture

Ingredient(s):

Chemical Name	Registration No.	CAS No.	EC No.	Concentration	Classification
Lead	N/A	7439-92-1	231-100-4	< 100%	Repr. 1A, H360 STOT RE 1, H372 Aquatic Acute 1 H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Antimony	N/A	7440-36-0	231-146-5	0.2 %	Not classified

Section 4 First aid measures

4.1 Description of first aid measures:

No hazards in case of an intact battery and using according the instructions. The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

In all cases of doubt, or when symptoms persist, seek medical attention.

4.1.1 In case of inhalation:

Remove to fresh air immediately. If breathing is difficult, give oxygen. Lead Compounds: Remove from exposure, gargle, wash nose and lips, consult physician.

Product name: Maintenance Free (MF), VRLA (MF), Conventional series – Dry Charged Lead

Version #: 3.0

SDS EU

Version #: 3.0

1 ssue date: 02.12.2019

2 / 15



4.1.2 In case of skin contact:

Flush with large amounts of water for at least 15 minutes, remove any contaminated clothing. If irritation develops seek medical attention. Lead Compounds: Wash with soap and water.

4.1.3 In case of eyes contact:

Flush immediately with water for 15 minutes, consult a physician. Lead Compounds: Flush immediately with water for 15 minutes, consult a physician.

4.1.4 In case of ingestion:

Do not induce vomiting, consult a physician immediately. Lead Compounds: Consult a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed:

Causes severe skin burns and eye damage. May damage fertility. May damage the unborn child. May cause harm to breastfed children.

Symptoms/injuries after inhalation : In case of repeated or prolonged exposure : May cause respiratory

irritation.

Symptoms/injuries after skin contact : Direct contact with internal components of a battery can be severely

> irritating to the skin and may result in redness, swelling, burns and severe skin damage. Skin contact may aggravate an existing dermatitis condition.

Skin contact may aggravate dermatitis.

: Dust from this product may cause eyes irritation. Symptoms/injuries Symptoms/injuries after eye contact

: Ingestion may cause nausea and vomiting. Abdominal pain. after ingestion

Diarrhea.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

Section 5 Fire-Fighting measures

5.1 Extinguishing media:

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire- If a battery ruptures, use

dry chemical, soda ash, lime, sand or carbon dioxide.

Unsuitable extinguishing media: None Know.

5.2 Special hazards arising from the substance or mixture

Fire hazard: On burning formation of metallic fumes. Battery may rupture due to pressure build-

up when exposed to excessive heat and may be result in lhe release of corrosive

materials

Hazardous decomposition products

in case of fire: Toxic gases and fumes may be released in a fire.

5.3 Advice for firefighters: Wear positive pressure self-contained breathing apparatus. Wear fully protective

suit.

SDS EU Product name: Maintenance Free (MF), VRLA (MF), Conventional series - Dry Charged Lead Version #: 3.0 Issue date: 02.12.2019 3/15



Section 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

General Measures: Avoid contact with spilled material. Do not touch damaged containers or spilled

material unless wearing appropriate protective equipment.

6.1.1 For non-emergency personnel: Use proper personal protective equipment as indicated in Section 8. Ensure

adequate ventilation. Avoid contact with eyes. Wear protective equipment. Keep

unprotected persons away.

6.1.2 For emergency responders: Wear positive pressure self-contained breathing apparatus if dust is generated.

6.2 Environmental Precautions: Do not allow product to reach sewage system or any water course. Inform

respective authorities in case of seepage into water course or sewage system. Do

not allow to enter sewers/ surface or ground water.

6.3 Methods for Containment and Cleaning

up:

In case the release occurs, stop flow of material: contain/absorb small spills with dry sand, earth, and vermiculite. If possible, carefully neutralize spilled electrolyte with soda ash, sodium bicarbonate, lime, etc. Wear acid-resistant clothing, boots, gloves, and face shield. Do not allow discharge of unneutralized acid to sewer. Spent Batteries - send to secondary lead smelter for recycling. Follow applicable federal, state and local regulations Neutralize as in preceding step. Collect neutralized

material in sealed container and handle as hazardous waste as

applicable.

6.4 Reference to other sections: See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Section 7 Handling and storage

7.1 Precautions for safe handling:

7.1.1 Protective measures:

Ensure good ventilation/exhaustion at the workplace. Avoid contact with eyes. Keep ignition sources away - Do not smoke. Due to the battery's low internal resistance and high power density, high levels of short circuit current can be developed across the battery terminals. Do not rest tools or cables on the battery. Use insulated tools only. Follow all installation instructions and diagrams when installing or maintaining battery systems.

7.1.2 Advice on general occupational hygiene:

nygiene:

Do not eat, drink and smoke in work areas. Wash hands after use. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including

any incompatibilities:

Store batteries in a cool, dry, well ventilated area that are separated from incompatible materials and any activities which may generate flames, sparks, or heat. Keep away from all metallic articles that could contact the negative and positive terminals on a battery and create a short circuit condition. Battery should be stored under roof for protection against adverse weather conditions. Store and handle only in areas with adequate water supply and spill control. Avoid damage to

battery case.

7.3 Specific end use(s): Not applicable.

Product name: Maintenance Free (MF), VRLA (MF), Conventional series – Dry Charged Lead

Version #: 3.0

SDS EU

4 / 15



Section 8 Exposure Controls/Personal Protection

8.1 Control parameters:

8.1.1 Occupational exposure limits:

Lead (7439-92-1)				
EU	European BEI	(Medium: blood - Time: no restriction - Parameter:		
		Lead (binding biological limit value)		
		0.075 mg/m3 (Medium: air - Time: 40 hours per week Parameter: Lead (TWA medical surveillance threshold in air measured as a time weighted average over 40 hours per week)		
		(Medium: blood - Time: no restriction – Parameter : Lead (medical surveillance threshold measured in individual workers		
Austria	MAK (mg/m3)	0.1 mg/m3 (inhalable fraction)		
Austria	MAK Short time value (mg/m3)	0.4 mg/m3 (inhalable fraction)		
Bulgaria	OEL TWA (mg/m3)	0.05 mg/m3		
Bulgaria	Bulgaria - BEI	300 µg/l (Medium: blood - Time: not lixed - Parameter: Lead (for women under 45 years old)		
-		400 μg/l (Medium: blood - Time: not fixed - Parameter: Lead)		
Croatia GVI (graniëna vrijednost izloZenosti) (mg/m3)		0.15 mg/m3		
Lead (7439-92-1)				
Croatia	Croatia - BEI	(Medium: blood - Time: not critical - Parameter: Lead (Medical surveillance should be carried out lyhen the limit value of Lead in blood of workers >40 µg/100mL blood)		
Cyprus	OEL TWA (mg/m3)	0.15 mg/m3		
Czech Republic	Expoziëni limity (PEL) (mg/m3)	0.05 mg/m3		
Czech Republic	Czech Republic - BEI	(Medium: urine - Time: discretionary - Parameter: 5 Aminolevulinic acid (For short term continual exposures <=30 calendar days)		
Denmark	Grænseværdie (langvarig) (mg/m3)	0.05 mg/m3 (dust, fume and powder)		
Denmark	Denmark - BEI	(Medium: blood - Parameter: Lead)		
Estonia OEL TWA (mg/m3)		0.1 mg/m3 (total dust)		
	,(9,)	0.05 mg/m3 (respirable dust)		
Finland	HTP-arvo (8h) (mg/m3)	0. 1 mg/m3 (all works)		
Finland	Finland - BEI	(Medium: blood - Time: not critical - Parameter: Lead)		



Lead (7439-92-1)		
France	VME (mg/m3)	0.1 mg/m3 (restrictive limit)
		400 μg/l (Medium: blood - Parameter: Lead (biological limit value, men)
_		300 μg/l (Medium: blood - Parameter: Lead (biological limit value, women)
France	France - BEI	200 μg/l (Medium: blood - Parameter: Lead (medical surveillance value, men)
		100 μg/l (Medium: blood - Parameter: Lead (medical surveillance value, women)
Cormony	TDCS 002 /DCW/)	300 μg/l (Medium: whole blood - Time: no restriction Parameter: Lead (women age below 45 years)
Germany	TRGS 903 (BGW)	400 μg/l (Medium: whole blood - Time: no restriction Parameter: Lead (women 45 years and older)
Gibraltar	OEL TWA (mg/m3)	0.15 mg/m3
		(Medium: blood - Time: no restriction - Parameter:Lead (binding biological limit value)
Gibraltar	Gibraltar - BEI	0.075 mg/m3 (Medium: air - Time: 40 hours per week Parameter: Lead (medical surveillance threshold measured in individual employees)
		(Medium: blood - Time: no restriction - Parameter:Lead (medical surveillance threshold measured in individual employees)
Greece OEL TWA (mg/m3)		0.15 mg/m3
Hungary	AK-érték	0.15 mg/m3
Ireland	OEL (8 hours ref) (mg/m3)	0.15 mg/m3
Ireland	OEL (15 min ref) (mg/m3)	0.45 mg/m3 (calculated)
Italy	OEL TWA (mg/m3)	0.075 mg/m3
Italy Italy - BEI		(Medium: blood - Time: end of workweek (Lead remediation must be performed when uorkers of fertile age have Lead in blood levels >40 µg/100mL)
Latvia	OEL TWA (mg/m3)	0.005 mg/m3
		(Medium: blood - Parameter: Lead (reference value in blood for occupationally unexposed population <=10 µg/100 mL)
Latvia	Latvia - BEI	(Medium: urine - Parameter: Coproporphyrin(reference value 22-57 μg/g Creatinine)
		(Medium: urine - Parameter: Aminolevulinic acid (reference value 0. 5-2.5mg/g Creatinine)



Lead (7439-92-1)		
Lithuania	IPRV (mg/m3)	0.15 mg/m3 (inhalable fraction) 0.07 mg/m3 (respirable fraction)
Luxembourg	OEL TWA (mg/m3)	0.15 mg/m3
Luxembourg	Luxembourg - BEI	(Medium: blood - Parameter: Lead) 0.075 mg/m3 (Medium: blood - Parameter: Lead (medical surveillance threshold in air measured as a time weighted average over 40 hours per week) (Medium: blood - Parameter: Lead (medical surveillance threshold measured in individual workers)
Poland	NDS (mg/m3)	0.05 mg/m3
Portugal	OEL TWA (mg/m3)	0.15 mg/m3 (mandatory indicative limit value)
Romania	OEL TWA (mg/m3)	0.05 mg/m3
Romania	OEL STEL (mg/m3)	0.10 mg/m3
Romania	Romania - BEI	150 μg/l (Medium: urine - Time: end of shift - Parameter: Lead) (Medium: blood - Time: end of shift - Parameter: Lead) (Medium: hair - Time: end of shift - Parameter: Lead) 10 mg/l (Medium: urine - Time: end of shift - Parameter: .delta Aminolevulinic acid) 300 μg/l (Medium: urine - Time: end of shift - Parameter: Coproporphyrin) (Medium: blood - Time: end of shift - Parameter::Erythrocytes protoporphyrin)
Slovakia	NPHV (priemerna) (mg/m3)	0.15 mg/m3
Slovakia	Slovakia - BEI	400 μg/l (Medium: blood - Time: not critical - Parameter: Lead) 100 μg/l (Medium: blood - Time: not critical - Parameter: Lead (women younger than 45 years of age) 15 mg/l (Medium: urine - Time: not critical - Parameter: .deltaAminolevulinic acid) 6 mg/l (Medium: urine - Time: not critical - Parameter: .deltaAminolevulinic acid (women younger than 45 years of age) 0.30 mg/l (Medium: urine - Time: nct critical Parameter: Coproporphyrins)
Slovenia	OEL TWA (mg/m3)	0.1 mg/m3 (inhalable fraction)
Slovenia	OEL STEL (mg/m3)	0.4 mg/m3 (inhalable fraction)
Spain	VLA-ED (mg/m3)	0.15 mg/m3



Lead (7439-92-1)			
Spain		(Medium: blood - Time: not critical - Parameter: Lead (3,K)	
Sweden	nivagränsvärde (NVG) (mg/m3)	0.1 mg/m3 (total inhalable dust) 0.05 mg/m3 (total respirable dust)	
United Kingdom	WEL TWA (mg/m3)	0.15 mg/m3	
United Kingdom	WEL STEL (mg/m3)	0.45 mg/m3 (calculated)	
Norway	Grenseverdier (AN) (mg/m3)	0.05 mg/m3 (dust and fume)	
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	0.05 mg/m3 (dust and fume)	
Switzerland	VME (mg/m3)	0.1 mg/m3 (inhalable dust)	
Switzerland VLE (mg/m3)		0.8 mg/m3 (inhalable dust)	
Switzerland	Switzerland - BEI	400 µg/l (Medium: whole blood - Time: no restrictions Parameter: Lead (men and women over 45 years old)	
		100 μg/l (Medium: whole blood - Time: no restrictions Parameter: Lead (women less than 45 years old,)	
Australia	TWA (mg/m3)	0.15 mg/m3 (dust and fume)	
Canada (Quebec) VEMP (mg/m3)		0.05 mg/m3	
Lead (7439-92-1)			
USA - ACGIH ACGIH TWA(mg/m3)		0.05 mg/m3	
Lead (7439-92-1)			
USA - IDLH	US IDLH (mg/m3	100 mg/m3	
USA - NIOSH	NIOSH REL (TWA) (mg/m3)	0.050 mg/m3	
USA - OSHA	OSHA PEL (TWA) (mg/m3)	50 μg/m3	

Antimony (7440-36-0)			
Austria MAK (mg/m3)		0.5 mg/m3 (inhalable fraction)	
Austria MAK Short time value (mg/m3)		5 mg/m3 (inhalable fraction)	
Belgium Limit value (mg/m3)		0.5 mg/m3	
Bulgaria	OEL TWA (mg/m3)	0.5 mg/m3	
Croatia	GVI (granièna vrijednost izloZenosti) (mg/m3)	0.5 mg/m3	



Czech Republic Expoziëni limity (PEL) (mg/m3)		0.5 mg/m3		
Denmark	Grænseværdie (langvari g) (mg/m3)	0.5 mg/m3 (powder)		
Estonia	OEL TWA (mg/m3)	0.5 mg/m3		
Finland	HTP-arvo (8h) (mg/m3)	0.5 mg/m3		
France	VME (mg/m3)	0.5 mg/m3		
Greece	OEL TWA (mg/m3)	0.5 mg/m3		
Hungary	AK-érték	0.5 mg/m3		
Hungary	CK-érték	2 mg/m3		
Ireland	OEL (8 hours ref) (mg/m3)	0.5 mg/m3		
Ireland	OEL (15 min ref) (mg/m3)	1.5 mg/m3 (calculated)		
Latvia	OEL TWA (mg/m3)	0.2 mg/m3 (metallic dust)		
Lithuania	IPRV (mg/ms)	0.5 mg/m3		
Netherlands	erlands Grenswaarde TGG 8H (mg/m3) 0.5 mg/m3			
Poland NDS (mg/m3) 0.5 mg/m3		0.5 mg/m3		
Portugal OEL TWA (mg/m3) 0.5 mg/m3		0.5 mg/m3		
Romania	OEL TWA (mg/m3)	0.20 mg/m3		
Romania	OEL STEL (mg/m3)	0.50 mg/m3		
Romania Romania - BEI 1 mg/l (Medium: urine - Time: end of shift - Para Antimony)		1 mg/l (Medium: urine - Time: end of shift - Parameter: Antimony)		
Slovakia	NPHV (priemernâ) (mg/m3)	0.5 mg/m3 (total dust)		
Slovenia	OEL TWA (mg/m3)	0.5 mg/m3 (inhalable fraction)		
Slovenia	OEL STEL (mg/m3)	2 mglms (inhalable fraction)		
Spain	VLA-ED (mg/m3)	0.5 mg/m3		
Sweden	nivàgränsvärde (NVG) (mg/m3)	0.25 mg/ms (total inhalable dust)		
United Kingdom	WEL TWA (mg/m3)	0.5 mg/m3		
United Kingdom	WEL STEL (mg/m3)	1.5 mg/m3 (calculated)		
Norway	Grenseverdier (AN) (mg/m3)	0.5 mg/m3		
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	0.5 mg/m3		
Switzerland	VME (mg/m3)	0.5 mg/m3 (inhalable dust)		



Antimony (7440-36-0)		
Australia	TWA (mg/m3)	0.5 mg/m3
Canada (Quebec)	VEMP (mg/m3)	0.5 mg/m3
USA - ACGIH	ACGIH TWA (mg/m3)	0.5 mg/m3
USA - IDLH	US IDLH (mg/m3)	50 mg/m3
USA - NIOSH	NIOSH REL (TWA) (mg/m3)	0.5 mg/m3
USA - OSHA	OSHA PEL (TWA) (mg/m3)	0.5 mg/m3

8.2 Exposure controls:

8.2.1Appropriate engineering controls: Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

8.2.2 Individual protection measures, such as personal protective equipment:

Eye/face protection: None needed under normal conditions. If battery case is damaged, use chemical

goggles or face shield.

Hand protection: None needed under normal conditions. If battery case is damaged, use rubber or

plastic acid-resistant gloves with elbow-length gauntlet.

Body protection:None needed under normal conditions. If battery case is damaged wear acid-resistant

apron. Under severe exposure or emergency conditions, wear acid

-resistant clothing and boots.

Respiratory protection: None required under normal conditions. When concentrations of sulfuric acid mist

are known to exceed PEL, use NIOSH or MSHA-approved respiratory protection.

Thermal hazards: Wear suitable protective clothing to prevent heat.



8.2.3 Environmental exposure controls: Do not allow product to reach sewage system or any water course. Inform respective

authorities in case of seepage into water course or sewage system. Do not allow to

enter sewers/ surface or ground water.

Product name: Maintenance Free (MF), VRLA (MF), Conventional series – Dry Charged Lead

Version #: 3.0 | Issue date: 02.12.2019 | 10 / 15



Section 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Appearance: Solid

Colour:Bluish grey metalOdour:Not availableOdour threshold:Not availablepH:Not available

Melting point/range (℃): 252,2222-360°C

Boiling point/range (℃): 1 380°C

Flash point (°C):

Evaporation rate:

Flammability limit - lower (%):

Flammability (solid, gas):

Ignition temperature (°C):

Upper/lower flammability/explosive limits:

Not available

Not available

Vapour pressure (20℃): 10 mm Hg

Vapour density at (20°C):

Relative Density: Not available Bulk density (kg/m³): 9,6-11,3 g/m3 Water solubility: Not available n-Octanol/Water (log Po/w): Not available Not available Auto-ignition temperature: Not available **Decomposition temperature:** Not available Viscosity, dynamic (mPa.s): **Explosive properties:** Not available Not available Oxidising properties: Molecular Formula: Not applicable **Molecular Weight:** Not applicable

9.2. Other information:

Fat solubility(solvent- oil to be specified)

etc: Not available
Surface tension: Not available
Dissociation constant in water(pKa): Not available
Oxidation-reduction Potential: Not available
Specific gravity: Not available



Section 10 Stability and reactivity

10.1 Reactivity:The substance is stable under normal storage and handling conditions.

10.2 Chemical stability: Stable at room temperature in closed containers under normal storage and handling

conditions.

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: Incompatible materials. High temperature, Sparks and other sources of ignition.

Avoid mixing acid with other chemicals.

10.5 Incompatible materials: Potassium, carbides, sulfides, peroxides, phosphorus, sulfurs, ketone, ester,

petrolatum. Reactive metals, strong bases, most organic compounds.

10.6 Hazardous decomposition products: Sealed batteries can emit hydrogen only if over charged (float voltage> 2.41 VPC).

The gas enters the air through the vent caps. To ABS: Temperatures over $300 \,^{\circ}\mathrm{C}$ (572 F) may release combustible gases. To PP: Temperatures over $380 \,^{\circ}\mathrm{C}$ (716 F) may release

combustible gases.

Section 11 Toxicological information

11.1 Information on toxicological effects:

Acute toxicity: Not classified

Antimony (7440-36-0)

LD50 oral rat 7 g/kg

Skin corrosion/Irritation: Not classified

Serious eye damage/irritation: Not classified

Respiratory or skin sensitization:

classified Germ cell mutagenicity:

Not

Not

Not

classified

Reproductive toxicity: May damage fertility. May damage the unborn child. May cause harm to breast-

fed children.

STOT- single exposure: Not

classified

STOT-repeated exposure: Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard: Not

classified

Product name: Maintenance Free (MF), VRLA (MF), Conventional series – Dry Charged Lead
Version #: 3.0 SDS EU

12 / 15



Section 12 Ecological information

12.1 Toxicity: Lead (CAS: 7439-92-1):

Acute t	oxicity	Time	Species	Remarks
LC50	0,44 mg/L	96h	Fish	Species: Cyprinus carpio [semi-static])
LC50	1.17 mg/l	96h	Fish	Species: Oncorhynchus mykiss [flow{hroughl)
EC50	0,6 mg/L	48h	Daphnia	Species: water flea

12.2 Persistence and degradability:Not available.12.3 Bioaccumulative potential:Not available.12.4 Mobility in soil:Persistant.

12.5 Results of PBT & vPvB assessment: The PBT and vPvB criteria of Annex XIII to the Regulation does not apply to inorganic

substances

12.6 Other adverse effects: Not available.

Section 13 Disposal considerations

13.1 Waste treatment methods: Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

Dispose of contents/container to comply with applicable local, national and

international regulations.

Recycling the product is recommended. Waste must be disposed of in accordance

with federal, stale, and local environmental control regulations.

Consult the appropriate local waste disposal expert about waste disposal. Since emptied containers retain product residue, follow label warnings even after

container is emptied.

Europeen waste code :16 06 01- - lead batteries

Section 14 Transport information

Section 14 Transport information			
	Land transport(ADR/RID)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN-Number	Not regulated for transport	Not regulated for transport	Not regulated for transport
UN Proper shipping name	Not applicable	Not applicable	Not applicable
Transport hazard Class	No	No	No
Packaging group	Not applicable	Not applicable	Not applicable
Environmental hazards	No	No	No
Special precautions for user	No	No	No
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable	Not applicable	Not applicable

Product name: Maintenance Free (MF), VRLA (MF), Conventional series – Dry Charged Lead Version #: 3.0 Issue date: 02.12.2019



Section 15 Regulation information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Contains no substances with Annex XVII restrictions

Dry Charge Lead Battery is not on the REACH Candidate List

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Other National regulations:

Germany

12th Ordinance Implementing the Federal

Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen

: Sulfuric acid is listed

SZW-lijst van mutagene stiffen

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Borstvoeding

: Lead is listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Vruchtbaarheid

: Lead is listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Ontwikkeling

: Lead is listed

Denmark

Recommendations Danish Regulation

: Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the product.

15.2 Chemical Safety Assessment

A chemical safety assessment has been carried out for the substance or the mixture

Section 16 Other information

16.1 Indication of changes:

Version 2.0 Amended by (EU) 2015/830

16.2 Training instructions:

Not applicable.

16.3 Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Product name: Maintenance Free (MF), VRLA (MF), Conventional series – Dry Charged Lead

Version #: 3.0

SDS EU

Version #: 3.0

14 / 15



16.4 Notice to reader:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard, Category 1	
Repr. 1A	Reproductive toxicity, Category 1A	
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1	
H360	May damage fertility or the unborn child	
H360Fd	May damage fertility. Suspected of damaging the unborn child	
H372	Causes damage to organs through prolonged or repeated exposure	
H400	Very toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	